

AGRIMAX TURF RT 333 - Data Sheet



Description

AGRIMAX TURF RT 333 (R-3+) is a radial tire designed for small tractors in gardening, vineyards and orchards applications. Its rounded shoulder design provides low soil compaction and makes it extremely delicate on the ground. Its unique extra-deep tread (R-3+) and the special design with directional blocks stand for excellent traction both in the field and on the road, and an extended tire life cycle. AGRIMAX TURF RT 333 (R-3+) ensures great self-cleaning properties and thanks to its low rolling resistance, allows for significant fuel saving.

UM

International Standard

Construction



RADIAL

Machinery

Agriculture: Orchard Harvester • Small Tractor • Vineyard Harvester

SIZE	Version	TRA Code	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
220/55 R 12	STANDARD		82 A8/B	7		221	550	249	1645	260	TL	E11-106R-007600
240/60 R 12	STANDARD		89 A8/B	7		242	592	269	1777		TL	E11-106R-007679
215/65 R 14	STANDARD		90 A8 / 90 B	W 7	W 6	220	630	290	1906	310	TL	E11-106R-0010331
200/65 R 16	STANDARD		94 A8/B	W6		202	666	309	2000	320	TL	E11-106R-007678
200/70 R 16	STANDARD	R1W	94 A8/B	W 6		200	686	317	2054	330	TL	E11-106R-008659
240/70 R 16	STANDARD		104 A8/B	W8	W 8 L ; W 9	244	742	340	2213	350	TL	E11-106R-007531
260/70 R 16	STANDARD		109 A8/109 B	W 8	W 8 L ; W 9	258	770	348	2287	370	TL	E11-106R-007158
280/70 R 16	STANDARD		112 A8/112 B	W9	W 8 ; W 10	289	800	359	2371	390	TL	E11-106R-006472
280/70 R 18	STANDARD		114 A8/114 B	W 9	W 8 ; W 10	289	840	390	2550	410	TL	E11-106R-006473
320/65 R 18	STANDARD		109 A8/109 B	W 10	W 9 ; W 11	319	873	394	2591	425	TL	E11-106R-007844
300/70 R 20	STANDARD		110 A8/110 B	W9	W10	295	952	431	2826	450	TL	E11-106R-006943
320/70 R 20	STANDARD		113 A8/113 B	W10	W9 ; W11	319	982	441	2916	450	TL	E11-106R-006944
380/70 R 20	STANDARD		122 A8/122 B	W 12	W 11 ; W 13	380	1082	486	3213	500	TL	E11-106R-007111
360/70 R 24	STANDARD		122 A8/122 B	W 11	W 10 ; W 12	357	1152	518	3409	550	TL	E11-106R-007110
380/70 R 24	STANDARD		125 A8/125 B	W 12	W 11 ; W 13	380	1190	534	3538	550	TL	E11-106R-007112
420/70 R 24	STANDARD		130 A8 / 130 B	W 13	W 12 ; W 14 L	418	1248	557	3728	575	TL	E11-106R-007206
420/85 R 24	STANDARD		137 A8 / 137 B	W 15 L	DW15L;DW14L	435	1324	594	3957	625	TL	E11-106R-0010344
340/85 R 28	STANDARD		127 A8 / 127 B	W 12	W11;DW11;DW12	370	1289	585	3874	625	TL	E11-106R-0010343
480/70 R 28	STANDARD		140 A8 / 140 B	W 15 L	W 14 L ; W 16 L	479	1421	631	4228	650	TL	E11-106R-009049
480/70 R 30	STANDARD		141 A8 / 141 B	W 15 L	W 14 L ; W 16 L	479	1478	660	4396	675	TL	E11-106R-009050
480/70 R 34	STANDARD		149 A8 / 149 B	W 15 L	W 14 L ; W 16 L	490	1580	723	4785	750	TL	E11-106R-009042

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 6/3/2025 12:32 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..