

AGRIMAX V-FLECTO - Technical Specifications



Description

AGRIMAX V-FLECTO is BKT's response to the challenging demand of both technology and performance for high-power tractors. This tire is perfect for soil tillage and haulage applications thanks to reduced soil compaction and self-cleaning properties. With the innovative VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tires, reaching high speeds. It also features the Narrow Rim Option that allows mounting standard rims on the tire. BKT has designed this tire with optimized geometry to enhance driving comfort both in the fields and on the road reducing fuel consumption.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: High-Power Tractor

Version	STANDARD
Type	TL
Tyre Size	VF 600/60 R 38 NRO
LI/SS	166 D

Dimensions US Standard

Usa code	94059126
Section Width (inch)	23.1
Overall Diameter (inch)	66.3
Static Loaded Radius (inch)	29.8
Rolling Circumference (inch)	200
Rim Rec	DW 20 B
Rim Alt	DW 18 L
Narrow Rim option	DW 18 L
ECE	E11-106R-005021
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29
45	5200	6050	7010	7860	8710	9570	10630
from 40 to 25	5720	6660	7700	8640	9580	10520	11700
20	5830	6790	7850	8810	9770	10720	11920
12	5940	6920	8000	8980	9950	10930	12150
5	6280	7320	8470	9500	10530	11560	12850
*Upto 5 Cyc with front loader	8000	9310	10780	12090	13400	14720	16360
5 HT	5830	6790	7850	8810	9770	10720	11920

* *For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 6/3/2025 12:24 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..