

AGRIMAX V-FLECTO - Technical Specifications



Description

AGRIMAX V-FLECTO is BKT's response to the challenging demand of both technology and performance for high-power tractors. This tire is perfect for soil tillage and haulage applications thanks to reduced soil compaction and self-cleaning properties. With the innovative VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tires, reaching high speeds. It also features the Narrow Rim Option that allows mounting standard rims on the tire. BKT has designed this tire with optimized geometry to enhance driving comfort both in the fields and on the road reducing fuel consumption.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: High-Power Tractor

Version	STANDARD
Type	TL
Tyre Size	VF 600/70 R 34 NRO
LI/SS	170 D

Dimensions US Standard

Usa code	94074785
Section Width (inch)	23.7
Overall Diameter (inch)	67.1
Static Loaded Radius (inch)	29.1
Rolling Circumference (inch)	198.4
Rim Rec	DW 21 B
Rim Alt	DW 20 B
Narrow Rim option	DW 18 B
ECE	E11-106R-008813
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29
45	6020	6980	7940	9030	9990	10950	12040
From 40 to 25	6610	7670	8730	9920	10980	12040	13230
20	6750	7810	8900	10120	11190	12270	13490
12	6880	7970	9070	10320	11410	12510	13760
5	7270	8430	9600	10910	12070	13240	14550
*Upto 5 Cyc with front loader	9260	10740	12210	13890	15370	16840	18520
5 HT	6750	7810	8900	10120	11190	12270	13490

* *For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 6/3/2025 12:22 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..