

# AGRIMAX V-FLECTO - Technical Specifications



## Description

AGRIMAX V-FLECTO is BKT's response to the challenging demand of both technology and performance for high-power tractors. This tire is perfect for soil tillage and haulage applications thanks to reduced soil compaction and self-cleaning properties. With the innovative VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tires, reaching high speeds. It also features the Narrow Rim Option that allows mounting standard rims on the tire. BKT has designed this tire with optimized geometry to enhance driving comfort both in the fields and on the road reducing fuel consumption.

## UM

US Standard

## Construction

 RADIAL

## Machinery

Agriculture: High-Power Tractor

Version	STEEL BELTED SPL
Type	TL
Tyre Size	VF 900/65 R 46 CFO
LI/SS	193 D

Dimensions US Standard

Usa code	94512713
Section Width (inch)	35.4
Overall Diameter (inch)	92
Static Loaded Radius (inch)	39.6
Rolling Circumference (inch)	275.7
Rim Rec	DW 30B
Narrow Rim option	DW 28 B
ECE	E11-106R-0010524

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29
45	11760	13600	15450	17530	19150	20760	23070
from 40 to 25	12930	14960	16990	19270	21040	22820	25350
20	13180	15260	17320	19640	21460	23270	25860
12	13440	15550	17660	20030	21880	23720	26370
5	14220	16450	18680	21190	23140	25100	27890
Upto 20 Cyc	14670	16960	19270	21860	23870	25890	28770
Upto 10 Cyc	17510	20260	23000	26100	28500	30910	34350
Upto 5Cyc	19190	22200	25220	28600	31240	33870	37640
5 HT	13180	15260	17320	19640	21460	23270	25860

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 6/3/2025 12:30 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..