

# AGRIMAXFACTOR - Technical Specifications



## Description

AGRIMAXFACTOR is BKT's brand-new 70 series for tractors that is perfect for both haulage and soil tillage operations. The improved tread design with further increased lug length and changed lug orientation stands for better roadability. The reduced lug angle ensures less rolling resistance, whilst the by 5 % increased contact area on the land significantly reduced the noise perception in the cabin – both features stand for more comfort. In addition, the strong polyester casing provides extraordinary lateral stability and a faster steering response even for high-speed operations or heavy-duty service. The tire's braking results on wet surface are excellent.

In a nutshell, AGRIMAXFACTOR's overall advantages are great handling in combination with under many aspects extraordinary driving comfort in addition to excellent durability – all particular requirements by increasingly heavier machinery including the higher weight of e-vehicles' battery packages. The exclusive sidewall shows the perfectly aligned "E-READY" logo that highlights BKT's commitment to electric mobility.

## UM

US Standard

## Construction

 RADIAL

## Machinery

Agriculture: Tractor

Version	STANDARD
Type	TL
Tyre Size	580/70 R 38
LI/SS	155 D/158 A8

## Dimensions US Standard

Usa code	94071050
Section Width (inch)	22.7
Overall Diameter (inch)	71.9
Static Loaded Radius (inch)	32.4
Rolling Circumference (inch)	214.8
Rim Rec	W 18 L
Rim Alt	DW18L;DD18L
ECE	E11-106R-007608
TRA Code	R1W

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23
40	4710	5470	6240	7010	7780	8540
30	4940	5740	6560	7360	8170	8970
25	5150	6000	6830	7680	8520	9360
20	5410	6290	7190	8070	8950	9830
5 LT	6300	7330	8370	9390	10430	11450
5 HT	5410	6290	7190	8070	8950	9830

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 6/3/2025 12:43 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..