

## AGRIMAXFACTOR - Technical Specifications



### Description

AGRIMAXFACTOR is BKT's brand-new 70 series for tractors that is perfect for both haulage and soil tillage operations. The improved tread design with further increased lug length and changed lug orientation stands for better roadability. The reduced lug angle ensures less rolling resistance, whilst the by 5 % increased contact area on the land significantly reduced the noise perception in the cabin – both features stand for more comfort. In addition, the strong polyester casing provides extraordinary lateral stability and a faster steering response even for high-speed operations or heavy-duty service. The tire's braking results on wet surface are excellent.

In a nutshell, AGRIMAXFACTOR's overall advantages are great handling in combination with under many aspects extraordinary driving comfort in addition to excellent durability – all particular requirements by increasingly heavier machinery including the higher weight of e-vehicles' battery packages. The exclusive sidewall shows the perfectly aligned "E-READY" logo that highlights BKT's commitment to electric mobility.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agriculture: Tractor

Version	STANDARD
Type	TL
Tyre Size	620/70 R 42
LI/SS	160 D/163 A8

# Dimensions International Standard

Section Width (mm)	625
Overall Diameter (mm)	1935
Static Loaded Radius (mm)	863
Rolling Circumference (mm)	5786
SRI (mm)	925
Rim Rec	DW 20 B
Rim Alt	DW18L ; W18L
ECE	E11-106R-007764
TRA Code	R1W

## Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
65	2475	2880	3285	3690	4095	4500
50	2600	3025	3450	3875	4300	4725
40	2715	3160	3600	4045	4490	4930
30	2850	3315	3780	4245	4710	5175
10 LT	3320	3860	4405	4945	5490	6030
10 HT	2850	3315	3780	4245	4710	5175

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 6/3/2025 12:44 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..