

RIDEMAX FL 693 M - Technical Specifications



Description

RIDEMAX FL 693 M is the ideal radial tire for those who frequently travel on the road with trailers/tank trucks. Actually designed for 75% on-the-road use, RIDEMAX FL 693 M provides excellent road performance prioritizing both comfort and self-cleaning properties. The speed index classes D/E of the range stands for higher speeds when travelling on the road leading to significant time savings. The low rolling resistance contributes to less fuel consumption, while a reinforced bead and steel belts ensure enhanced durability.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Tanker • Trailer

Version	STANDARD
Type	TL
Tyre Size	500/60 R 22.5
LI/SS	155 D/152 E

Dimensions US Standard

Usa code	94040605
Section Width (inch)	19.8
Overall Diameter (inch)	46.1
Static Loaded Radius (inch)	20.9
Rolling Circumference (inch)	140.8
Rim Rec	AG 16.00
Rim Alt	15.00 ; 17.00
ECE	E4-106R-001402

Load capacity (lbs)

mph / psi	15	17	23	29	35	41	46	52	58
45	2910	3300	3910	4620	5290	5870	6580	7210	7830
40	3160	3590	4280	5050	5780	6420	7180	7860	8540
30	3840	4340	5170	6110	6990	7760	8690	9510	10340
25	4310	4880	5810	6860	7850	8720	9770	10690	11620
15	5000	5680	6760	7970	9120	10130	11340	12420	13500
5	5700	6460	7690	9080	10380	11540	12920	14150	15380

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 6/3/2025 11:54 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..