

RIDEMAX FL 693 M - Technical Specifications



Description

RIDEMAX FL 693 M is the ideal radial tire for those who frequently travel on the road with trailers/tank trucks. Actually designed for 75% on-the-road use, RIDEMAX FL 693 M provides excellent road performance prioritizing both comfort and self-cleaning properties. The speed index classes D/E of the range stands for higher speeds when travelling on the road leading to significant time savings. The low rolling resistance contributes to less fuel consumption, while a reinforced bead and steel belts ensure enhanced durability.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Tanker • Trailer

Version	HD
Type	TL
Tyre Size	600/55 R 26.5
LI/SS	177 D

Dimensions International Standard

Section Width (mm)	611
Overall Diameter (mm)	1333
Static Loaded Radius (mm)	586
Rolling Circumference (mm)	4077
SRI (mm)	625
Rim Rec	AG 20.00
ECE	E11-106R-003007

Load capacity (Kg)

km/h / bar	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	5.0	6.0
65	2265	2705	3285	3800	4380	4965	5330	5915	6500	6865	7300
50	2740	3270	3980	4595	5305	6010	6450	7160	7865	8305	8835
40	3080	3675	4470	5165	5960	6755	7250	8045	8840	9335	9930
30	3420	4080	4965	5735	6615	7500	8050	8935	9815	10365	11025
25	3580	4270	5195	6000	6925	7845	8425	9345	10270	10845	11535
10	4075	4865	5915	6835	7885	8940	9595	10645	11695	12355	13140

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 6/3/2025 11:57 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..