

RIDEMAX FL 693 M - Technical Specifications



Description

RIDEMAX FL 693 M is the ideal radial tire for those who frequently travel on the road with trailers/tank trucks.

Actually designed for 75% on-the-road use, RIDEMAX FL 693 M provides excellent road performance prioritizing both comfort and self-cleaning properties. The speed index classes D/E of the range stands for higher speeds when travelling on the road leading to significant time savings. The low rolling resistance contributes to less fuel consumption, while a reinforced bead and steel belts ensure enhanced durability.

UM

International Standard

Construction



Machinery

Agriculture: Tanker • Trailer

Version	STANDARD
Туре	TL
Tyre Size	850/50 R 30.5
LI/SS	182 D

Dimensions International Standard

Section Width (mm)	862
Overall Diameter (mm)	1625
Static Loaded Radius (mm)	719
Rolling Circumference (mm)	4925
SRI (mm)	725
Rim Rec	AG 28.00
ECE	E4-106R-001500

Load capacity (Kg)

km/h / bar	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	2865	3250	3945	4565	5260	5960	6425	7120	7735
65	3145	3570	4335	5015	5780	6545	7055	7820	8500
50	3810	4320	5250	6070	6995	7920	8540	9465	10285
40	4280	4860	5900	6825	7865	8905	9595	10640	11560
25	4975	5645	6850	7925	9135	10345	11150	12360	13430
10	5665	6430	7805	9030	10405	11785	12700	14080	15300

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 6/3/2025 11:59 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..