

RIDEMAX FL 693 M - Technical Specifications



Description

RIDEMAX FL 693 M is the ideal radial tire for those who frequently travel on the road with trailers/tank trucks. Actually designed for 75% on-the-road use, RIDEMAX FL 693 M provides excellent road performance prioritizing both comfort and self-cleaning properties. The speed index classes D/E of the range stands for higher speeds when travelling on the road leading to significant time savings. The low rolling resistance contributes to less fuel consumption, while a reinforced bead and steel belts ensure enhanced durability.

UM

US Standard

Construction



RADIAL

Machinery

Agriculture: Tanker • Trailer

Version	STANDARD
Type	TL
Tyre Size	850/50 R 30.5
LI/SS	182 D

Dimensions US Standard

Usa code	94034505
Section Width (inch)	33.9
Overall Diameter (inch)	64
Static Loaded Radius (inch)	28.3
Rolling Circumference (inch)	193.9
Rim Rec	AG 28.00
ECE	E4-106R-001500

Load capacity (lbs)

mph / psi	15	17	23	29	35	41	46	52	58
45	6320	7160	8700	10060	11600	13140	14160	15700	17050
40	6930	7870	9560	11060	12740	14430	15550	17240	18740
30	8400	9520	11570	13380	15420	17460	18830	20870	22670
25	9440	10710	13010	15050	17340	19630	21150	23460	25480
15	10970	12440	15100	17470	20140	22810	24580	27250	29610
5	12490	14170	17210	19910	22940	25980	28000	31040	33730

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 6/3/2025 11:59 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..