

XL GRIP (L3) - Data Sheet



Description

XL GRIP (E-3/L-3) is a wide-base bias-ply tire for loaders designed to minimize cuts and punctures in heavy-duty loading applications. It provides exceptional traction as well as an extended tire life.

UM

International Standard

Construction

✚ BIAS

Machinery

Industrial: Loader

OTR: Dozer • Loader

SIZE	Version	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	Tread Depth
16.0/70 - 20	STANDARD	L3	16	13 SDC		405	1090	480	3295	TL	26
15.5 - 25	STANDARD	E3/L3	12	12.00/1.3	12.00/1.3 (DC)	402	1285	573	3767	TL	25
17.5 - 25	DUAL BEAD	E3/L3	24	14.00/1.5		435	1345	622	3980	TL	30
17.5 - 25	DUAL BEAD	E3/L3	20	14.00/1.5		435	1345	622	3980	TT	30
17.5 - 25	DUAL BEAD	E3/L3	20	14.00/1.5		435	1345	622	3980	TL	30
17.5 - 25	STANDARD	E3/L3	12	14.00/1.5		435	1345	622	3980	TL	30
17.5 - 25	STANDARD	E3/L3	16	14.00/1.5		435	1345	622	3980	TL	30
17.5 - 25	STANDARD	E3/L3	20	14.00/1.5		435	1345	622	3980	TL	30
20.5 - 25	STANDARD	E3/L3	12	17.00/2.0		530	1485	682	4395	TL	32
20.5 - 25	STANDARD	E3/L3	16	17.00/2.0		530	1485	682	4395	TL	32
20.5 - 25	STANDARD	E3/L3	20	17.00/2.0		530	1485	682	4395	TL	32
20.5 - 25	STANDARD	E3/L3	24	17.00/2.0		530	1485	682	4395	TL	32
23.5 - 25	ARAMID BELTED HD	E3/L3	24	19.50/2.5		600	1625	742	4810	TL	36
23.5 - 25	STANDARD	E3/L3	16	19.50/2.5		600	1625	742	4810	TL	36
23.5 - 25	STANDARD	E3/L3	20	19.50/2.5		600	1625	742	4810	TL	36
23.5 - 25	STANDARD	E3/L3	24	19.50/2.5		600	1625	742	4810	TL	36
26.5 - 25	STANDARD	L3	20	22.00/3.0		680	1740	796	5150	TL	36
26.5 - 25	STANDARD	L3	28	22.00/3.0		680	1740	796	5150	TL	36
26.5 - 25	STANDARD	L3	32	22.00/3.0		680	1740	796	5150	TL	36
29.5 - 25	STANDARD	L3	28	25.00/3.5		760	1860	849	5544	TL	39
29.5 - 25	STANDARD	L3	32	25.00/3.5		760	1860	849	5544	TL	39

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 6/3/2025 12:46 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..